

Parameters

Visual characteristics

Pixel pitch	3.9	mm
Pixel configuration	SMD 3 in 1	--
Brightness	≥1200	nits
Refresh frequency	≥2000	Hz
Gray scale	32768	level
Colors	35	trillion
Ingress protection (Front / Rear)	IP40/IP21	--
Viewing angle (H/V)	140/140	deg.
Power consumption (max/avg)	540/180	w/sq.m.

Modular characteristics

Cabinet size (W×H×D)	500×500×96	mm
Cabinet weight	20.2	Lbs
Cabinet panel material	Aluminum-alloy	
pixel matrix per cabinet	128×128	pixels

Environment

Input voltage (AC)	110 ~ 240 V	V
Operating temperature	-10 ~ +40	°C
Signal input format (with video processor)	AV, S-Video, VGA, DVI, HDMI, SDI,DP	

★ Shenzhen Absen Optoelectronic Co., Ltd. reserves the right to modify product design, specifications, and parameters without further notice. Photos are used for illustration purpose only as products may differ from these photos. All rights reserved by Shenzhen Absen Optoelectronic Co., Ltd.

Applications

Indoor stages, exhibitions and where need HD indoor displays. TV stations, concerts, theme parks, exhibitions and so on where needing HD displays, install and dismantle, easily.

